

TENDER ENQUIRY NO. FCS/NSR/TE/026/26

PRICE TERM SHEET							
01	02	03	4	5	6	7	8
S. NO.	DESCRIPTION	Quantity	Unit	UNIT PRICE F.O.R. (without GST)	TOTAL PRICE F.O.R. (without GST)	GST @18%	TOTAL VALUE F.O.R. (Including GST)
1	LPG Regulator 20 Nos	24	Num				
2	LPG Regulator 22 Nos	36	Num				
3	MS (Mild Steel) Iron Kassi (Agricultural spade/hoe) Blade Material: Hot-rolled or drop-forged Mild Steel (MS), edge-hardened (tempered) to retain sharpness. Standard Blade Size: 9" x 10". Average Weight: 2 kg (excluding the handle). Eyelet (Peen) Diameter: 1.7" tapered to tightly lock the handle in place. Finishing: Coated with anti-rust black bitumen, powder coating, or industrial enamel paint to prevent oxidation	21	Num				
4	MS (Mild Steel) Shovel with Wooden handle Blade Material: Pressed or hot-rolled Mild Steel (MS). Blade Thickness: approx 2 mm. Hardness Rating: Tempered along the front leading edge to a minimum of 35 to 48 HRC to prevent curling or denting when scraping stone aggregate or hard concrete surfaces.	21	Num				
5	MS (Mild Steel) Pick-axe with Wooden handle, Head Configuration: Dual-sided geometry featuring a sharp chisel edge on one tip (for cutting roots and prying) and a pointed pick on the opposing end (for fracturing rock/hard clay). Hardness Rating: Typically tempered along the working ends to an HRC rating of 48 to 52 to preserve edge retention without rendering the core body brittle. Eyelet Design (Oval/Round Eye): Center eyelet features a standardized tapered slip-fit collar (generally 50mm x 70mm oval diameter). The handle slides down from the top, mechanically wedging itself tighter with every downward strike to prevent the head from slipping off. Surface Coating: Sealed in thick anti-corrosive powder paint or black bitumen enamel to halt environmental rusting when left in outdoor work zones. Head Weight: approx 2.5 kg Length of Pick-axe (without handle) tip-to-tip: 550-600 mm Handle: Made of hardwood Length of handle: 3 ft	15	Num				

6	Silky Scarf (Romal) Size: 54"x 54 " Purpose: To be worn by welders on head and around neck under protective gear/equipment/cap Material: Soft Cloth, Silk & Fiber Mix (7/8 Micron)	336					
7	Welding Umbrella 10' With Cloth Fine Quality	20	Num				
8	: Leather Gloves 16" Material: premium grain leather Length: 14" total with extended cuff for protection of forearm Thickness: 1.4 mm	300	Num				
9	Cotton Gloves Size: 9 No. (Large) Length: 10" Width across palm: 5" Weight: 50 gram per pair Cuff style: open/safety cuff for easy on and off Grip Enhancement	300	Prs				
10	M.S Jali (Mesh) Size 4' x 8'	20	Num				
11	Ice Box (non-electrical) Size: 3' x 1-1/2' x 1-1/2' Capacity: 100 litres Outer & Inner Shell Material: High-Density Polyethylene (HDPE). Must be UV-stabilized, impact-resistant, and certified FDA Food-Grade / BPA-Free. Insulation Core Material: Closed-cell, pressure-injected Polyurethane (PU) Foam Wall/Lid Thickness: Heavy-Duty Rotomolded: 2.0 inches to 2.56 inches (50 mm to 65 mm). Manufacturing Construction: Seamless, single-piece molded outer structure (eliminates glued seams where heat can easily penetrate) Temperature Maintenance/Ice Retention Duration: 10-12 hours	7	Num				
12	100% Polyester webbing Anti Slip, Strong Grip, Durable, Washable Safety Factor Ratio 7:1, Light Weigh	4	Num				
13	Web Sling Belt Capacity 15 Ton WLL. Length 6 meters. Thickness 4-ply (Quad wall). 100% Polyester webbing. Anti Slip, Strong Grip, Durable & Washable	4	Num				
14	LPG Gas Pipe H.P Size ½"	30	Mtr				
15	Latta Cloth Soft Fine Quality (50 Mtr Roll)	4	Roll				
16	Disposable Cup, Hard Card Paper, Fine Quality	2000	Num				

17	Cotton Rags Fine Quality Size: 1' x 1' Purpose: oversized, heavy-duty cleaning cloths to provide a large surface area for absorbing heavy spills, wiping machinery, and handling grease.	30	Kgs				
18	Burner Batti (Heat Lamp) LPG or natural gas-fired infrared ceramic heater Material: Cordierite with 50 RFT Pipe DA & Oxygen regulators (Complete), Heavy Duty , Tip Cleaner , HI- Quality Flame for welding	2	Num				
19	Foam sheet size: 6 ft (Length) x 4ft (Width) x4" (Thickness) Material: High Density Polyurethane Durable, Comfortable, Breathable Fine Quality	12	Num				
20	Water Cooler Capacity : 30 liter Material: Food grade BPE-Free High Density Polyethylene (HDPE) outer shell with inner Polypropylene liner. Insulation: The core layer injected with dense Thermopore / Polyurethane foam to offer up to 6-8 hours of cooling/Temperature maintenance	2	Num				
21	Pipe Lifting Belt Capacity 25 Ton vertical working load limit (WLL). Length 6 meters. Width 12 inches 4-ply thickness. 100% Polyester webbing. Anti Slip, Strong Grip, Durable & Washable. Safety Factor Ratio 7:1, Light Weight	1	Num				
Total					-	-	-