

TENDER ENQUIRY NO. FCS/KK/TE/012/26

PRICE TERM SHEET							
01	02	03	4	5	6	7	8
S. NO.	DESCRIPTION	Quantity	Unit	UNIT PRICE F.O.R. (without GST)	TOTAL PRICE F.O.R. (without GST)	GST @18%	TOTAL VALUE F.O.R. (Including GST)
1	Grinder Switch 2400 watt typically require an Electrical rating: 12A to 15A Rated Voltage: 250V Endurance Rating: 5E4 Safety Feature: Deadman paddle triggers	10	Num				
2	Canvas Turpal (Tarpaulin) Size: 25' x 50' Material: Cotton-Poylester blend for durability Weight: 20 oz per square yard Treatment: wax treated for water proofing (minimum 24 hour water proof) Features: rust-resistant brass grommets (eyelets) spaced every 24 to 36 inches along the perimeter, with double-stitched lock seams for reinforcement.	6	Num				
3	Polythene Sheet Material: HDPE Thickness: 0.8mm ± 0.02 mm (800 Microns) Weight: 750-800 GSM Required form: in long continuous rolls Roll weight: 24Kg Roll	14	Rol				
4	G.I.Box Size 6 ft (Length) × 3 ft (Width) × 3 ft (Height) Sheet Thickness: 22 Gauge (approx. 0.79 mm or 0.0312 inches in steel thickness) Strong handles for lifting on either side. Locking strip on front. fine/heavy-duty stitching	5	Num				

5	Silky Scarf (Romal) Size: 54"x 54 " Purpose: To be worn by welders on head and around neck under protective gear/equipment/cap Material: Soft Cloth, Silk & Fiber Mix (7/8 Micron) Brand: Double Horse or equivalent	400	Num				
6	Welding Canopy Attested Wire Proof Size 36' x 36' Fire Proof	6	Num				
7	Water Cooler Capacity : 100 liter Material: Food grade BPE-Free High Density Polyethylene (HDPE) outer shell with inner Polypropylene liner. Insulation: The core layer injected with dense Thermopore / Polyurethane foam to offer up to 6-8 hours of cooling/Temperature maintenance Anti Fungus	7	Num				
8	Canvas Turpal (Tarpaulin) Size: 30' x 38' Material: Cotton-Polyester blend for durability Weight: 20 oz per square yard Treatment: wax treated for water proofing (minimum 24 hour water proof) Features: rust-resistant brass grommets (eyelets) spaced every 24 to 36 inches along the perimeter, with double-stitched lock seams for reinforcement.	5	Num				
TOTAL RS.					-	-	-