

BILL OF QUANTITIES (BOQ)

PROCUREMENT SUPPLY & PLACEMENT OF 33 NOS FIRE PROOF SAFE & FIRE PROOF ALMIRAH AT VARIOUS NBP

BRANCHES

S. No.	Description	Quantity (a)	Unit (b)	Unit Rate (c) (Rs)	Total (a x c) (Rs)
1.	Supply of fire proof steel Almirah of size 72"x42"x24" having four shelves and fabricated with Outer side M.S sheet 3.18mm with four (04Nos.) fixed shelves using 1.59mm , inner side 1.2mm and slab thickness 2" inch inner side partition built-in standard brass triple lock with stainless steel keys with 2" dia pin 11 Nos. in both panels moving inward and outward with mechanical system. The Pins should be firmly fixed in holes along with four stainless steel large size handles. The main front frame should be 6mm thick M.S Patti. The handle of Almirah should be chromium handles. The Space between inner and outer should be filled with fire proof material and almirah should be painted with silver hammer paint. Brass made 2" made of solid iron, shaft, cold drawn steel double control lock key system, hammer silver paint The rates should include along with all govt. taxes. Transportation charges loading / unloading to Bank / Branch & Placing at desired location included. complete in all respect as per NBP & SBP approved standards Comply ATSM E119 FD120 rating	14	Nos		
2.	Supply of safe size of 72x36x36" having outside body made from 6.5mm thick M.S sheet, inner body of 1.4mm M.S sheet having minimum space 2-3 inches of space between sheets for the fire proof material consisting of asbestos, abrak spaces all around safe with stainless steel imported heavy duty handles as well as system, heavy duty locks are of brass with stainless steel or brass white keys. Main door are consisted of ¼ thick hard steel sheet supported with ¼ frame border at least 4 inches wide added 3/16 thick strip along with 14 SWG brass / copper sheet to avoid the drilling & fire cutting in lock area with standard mechanical mechanism having 1.5 inch steel bar. Attached with heavy duty brass cum steel locks 2-in quantity with heavy duty steel keys with triple control locking system. Outer body is partially attached with forged iron strip all around the steel vault. This will save the outer body from any sort of drill fire cutting etc. with stainless steel imported heavy duty handles as well as separate holders of same quality and specifications, inside portable or as per demand fixed shelves will be provided. Main doors are provided with triple controlled heavy duty locks. Front door & back side from inside is totally covered with 0-grind pits 22 SWG stainless steel (Japanese) adopting Chubb style, a brand name in steel security equipment's in the World. Fire endurance Test= Internal temp. not more than 62 Deg C with a humidity not exceeding 80% after 1-hour exposure to a severe fire.	19	Nos		

Fire proof rating = 120- minutes at 2000 F (1090 C). Drop Test = Dropped from 30 ft height. i/c all Govt. taxes and transportation, Loading /unloading & placement at desired location in NBP branch. (Complete in all respect @ NBP Standard w.r.t State Bank of Pakistan)				
--	--	--	--	--

Amount in Words (RS. _____

_____)

Total Amount Rs.

Total Amount in Words (RS.

_____)

- The quoted rates / amount shall be inclusive of all applicable Federal/Provincial Govt. Taxes/Duties and charges for inland transportation and other related services etc. as specified in the Clause 16 or 17 of the BDS.
- The Bidder will ensure the Inspection of Material/Items as mandatory prior or after delivery at designated NBP branches /offices.
- The material upon delivery at the site should be got verified from the Bank Engineer; prior to its installation/placement at site. Otherwise, Bank Engineer reserves the right to replace the same without incurring any liability or payment of any charges to the bidder.
- Photograph of fire proof Almirah & Fire Proof Safe after Placement at designated branch or office be attached with final bill.

